



MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Copper Anti-Seize and Lubricating Compound

Product Number (s): SL35901, SL35903, 72901

Product Use: Anti-seize and lubricating compound

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

1-215-674-4300(General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

www.crc-canada.ca

1-905-670-2291

In Mexico:

CRC Industries Mexico

Av. Benito Juárez 4055 G

Colonia Orquídea

San Luís Potosí, SLP CP 78394

www.crc-mexico.com

52-444-824-1666

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Copper semi-solid paste with petroleum odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause irritation.

SKIN: For hypersensitive persons, this product may irritate the skin after prolonged periods of time.

INHALATION: Viscous nature may block breathing passages if inhaled.

INGESTION: May cause diarrhea.

CHRONIC EFFECTS: None known

TARGET ORGANS: None known

Medical Conditions Aggravated by Exposure: Pre-existing skin sensitivities

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Copper Anti-Seize and Lubricating Compound

Product Number (s): SL35901, SL35903, 72901

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Petroleum oil	64742-57-0 / 64742-52-5	60 – 70
Nonhazardous blend	82980-54-9 / 471-34-1 / 14807-96-6	25 – 40
Graphite	7782-42-5	1 – 10
Copper powder	7440-50-8	1 – 10

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Wash out mouth immediately. Consult physician.

Note to Physicians: Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: As defined by OSHA, this product is not flammable.

Flash Point: 430°F / 221°C (COC) Upper Explosive Limit: 7.0
Autoignition Temperature: > 500°F / > 260°C Lower Explosive Limit: 0.9

Fire and Explosion Data:

Suitable Extinguishing Media: Foam, dry powder, Halon®, carbon dioxide, sand, earth & water mist. Do not use water jet.

Products of Combustion: Smoke, soot, hydrocarbons and oxides of carbon, sulfur & nitrogen.

Explosion Hazards: Containers, when exposed to heat from fire, may build pressure and rupture.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate

Product Name: Copper Anti-Seize and Lubricating Compound**Product Number (s): SL35901, SL35903, 72901**

respiratory protection. Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

Section 7: Handling and Storage

Handling Procedures: Do not use near sources of ignition. Provide adequate ventilation during use. Wear appropriate personal protective equipment. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Containers should be tightly closed while in storage.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection**Exposure Guidelines:**

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Petroleum oil	5*	NE	5*	NE	NE		mg/m ³
Nonhazardous blend	NE	NE	NE	NE	NE		
Graphite	2.5 (v)	NE	2	NE	2.5	NIOSH	mg/m ³
Copper powder	1	NE	0.1	NE	1	NIOSH	mg/m ³
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated * – oil mist							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: semi-solid paste

Color: copper/bronze

Odor: petroleum

Odor Threshold: ND

Specific Gravity: 1.09

Initial Boiling Point: > 500°F / > 260°C

Product Name: Copper Anti-Seize and Lubricating Compound**Product Number (s): SL35901, SL35903, 72901**

Freezing Point: ND
 Vapor Pressure: < 0.01 kPa
 Vapor Density: > 5 (air = 1)
 Evaporation Rate: very slow
 Solubility: negligible in water
 Coefficient of water/oil distribution: ND
 pH: NA
 Volatile Organic Compounds: wt %: 0 g/L: 0 lbs./gal: 0

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition, temperature extremes

Incompatible Materials: Strong inorganic and organic acids, oxidizing and copper reactive agents

Hazardous Decomposition Products: Smoke, airborne soot hydrocarbons and oxides of carbon, sulfur & nitrogen

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Petroleum oil	> 5000 mg/kg	> 5000 mg/kg	No data
Nonhazardous blend	No data	No data	No data
Graphite	No data	No data	No data
Copper powder	No data	No data	No data

Chronic Toxicity:

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Petroleum oil	No	No	No	E (mild) / S (mild)	No
Nonhazardous blend	No	No	No	Unknown	Unknown
Graphite	No	No	No	E (mild) / S (mild)	Unknown
Copper powder	No	No	No	E (mild) / S (moderate) / R (moderate)	Unknown

E – Eye	S – Skin	R - Respiratory
---------	----------	-----------------

Reproductive Toxicity: No information available
Teratogenicity: No information available
Mutagenicity: No information available
Synergistic Effects: No information available

Product Name: Copper Anti-Seize and Lubricating Compound

Product Number (s): SL35901, SL35903, 72901

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: In extreme cases, may generate fractions that could act as a marine pollutant.

Persistence / Degradability: No information available

Bioaccumulation / Accumulation: Bioaccumulation potential nil.

Mobility in Environment: Highly unlikely to cause widespread contamination.

Section 13: Disposal Considerations

Waste Classification: This product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)
Empty containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): Not Regulated

ICAO/IATA (air): Not Regulated

IMO/IMDG (water): Not Regulated

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Copper (5,000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	No
	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

Product Name: Copper Anti-Seize and Lubricating Compound

Product Number (s): SL35901, SL35903, 72901

1986 and 40 CFR Part 372:
Copper (< 10%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Occupational Safety and Health Administration:

This product is regulated under the Hazard Communication Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None

Consumer Products VOC Regulations: This product is not regulated.

State Right to Know:

New Jersey: 7440-50-8, 7782-42-5, 471-34-1

Pennsylvania: 7440-50-8, 7782-42-5, 471-34-1

Massachusetts: 7440-50-8, 7782-42-5, 471-34-1

Rhode Island : 7440-50-8, 7782-42-5, 471-34-1

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: This product is not regulated.

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)	
Health:	1
Flammability:	1
Reactivity:	1
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
CRC #: SL35901
Revision Date: 04/02/2013

Changes since last revision: Revision Date

Product Name: Copper Anti-Seize and Lubricating Compound

Product Number (s): SL35901, SL35903, 72901

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists	NA: Not Applicable
CAS: Chemical Abstract Service	ND: Not Determined
CFR: Code of Federal Regulations	NIOSH: National Institute of Occupational Safety & Health
DOT: Department of Transportation	NFPA: National Fire Protection Association
DSL: Domestic Substance List	NTP: National Toxicology Program
g/L: grams per Liter	OSHA: Occupational Safety and Health Administration
HMIS: Hazardous Materials Identification System	PMCC: Pensky-Martens Closed Cup
IARC: International Agency for Research on Cancer	PPE: Personal Protection Equipment
IATA: International Air Transport Association	ppm: Parts per Million
ICAO: International Civil Aviation Organization	RoHS: Restriction of Hazardous Substances
IMDG: International Maritime Dangerous Goods	STEL: Short Term Exposure Limit
IMO: International Maritime Organization	TCC: Tag Closed Cup
lbs./gal: pounds per gallon	TWA: Time Weighted Average
LC: Lethal Concentration	WHMIS: Workplace Hazardous Materials Information System
LD: Lethal Dose	